

# POWER CROWN REMOVERS

# Reorder #4638

## CONTENTS

1 Power Crown Remover™ - Left 1 Power Crown Remover™ - Right 10pcs 2.0 mm High-Speed Diamond Drill Burs - Silver

### USE

Aids in the removal of any temporary or permanently bonded crowns.

## **PRIOR TO USE**

- Inspect the instrument for any sign of damage, wear, or defects before each use.
- Sterilize before each use. Steam sterilize at 270°F/132°C for 4 minutes or 250°F/121°C for 30 minutes.
- Recommended: Allow 30 minutes of dry time after the sterilization cycle.
- Do not heat above 320°F/160°C. Use recommended chemicals only.
- Use only manufacturer-approved cleaning agents.
- Detailed care and maintenance instructions available upon request or go to powerdentalgroup.com.

## CAUTION

- Ensure each hole is completely drilled through the crown.
- If the crown is securely bonded, a third hole on the lingual may be necessary.

## DIRECTIONS

### STEP 1

**Drill Access Hole:** Drill a 2 mm diameter hole onto the occlusal surface of the crown, deep enough for the Power Crown Remover gold post to contact the tooth.

#### STEP 2

**Prepare a Purchasing Point:** Drill a purchasing point on the buccal or lingual as close to the gingiva as possible, for the talon to grasp.

#### Note: No drilled hole is necessary if working margin is available.

#### STEP 3

**Buccal Side Use:** For crown removal on anterior teeth, use the Power Crown Remover with the talon facing the buccal side.

#### STEP 4

**Position the Tools:** Hook the talon into the buccal or lingual purchase point or existing margin, then position the gold tip into the 2 mm occlusal hole. **Note: If removing a bridge, drill holes on the buccal side near the mesial and distal ends of the bridge to facilitate effective removal.** 

#### STEP 5

Squeeze and Remove: Apply subtle pressure apically and remove the crown.

## MAINTENANCE

- Inspect instruments after cleaning and replace if damaged or worn.
- For optimal precision return to Power Dental for sharpening if the working edge becomes dull.
- Lubricate hinges as necessary.
- Replace burs as necessary if they become worn.















Step 5